



TUFLUOR® PTFE CHEM FORM

© 2015 THE CHEMOURS COMPANY.
CHEMOURS™ AND TEFLON™ ARE
TRADEMARKS OF THE CHEMOURS
COMPANY. TEFLON™ IS USED UNDER
LICENSE BY TUBIGOMMA DEREGIBUS SRL
SOCIETÀ UNIPERSONALE



WIDE CORRUGATED, BLACK,
CONDUCTIVE, CLOTH FINISH EPDM
STAINLESS STEEL WIRE HELICES
SYNTHETIC PLIES
SMOOTH, CO-EXTRUDED CLEAR/
WHITE PIGMENTED TEFLON™ PTFE

Suction and delivery hose designed according to EN 12115 standards for chemicals and solvents, except for chlorine trifluoride, chlorine and fluorine gas, oxygen difluoride, phosgene and molten alkalis (for ex. sodium). Designed for the chemical industry, foodstuff, pharmaceutical and cosmetic industry, where a flexible connection is required. The hose is produced with high quality elastomers, with excellent chemical and mechanical properties. Not intended for use as an implant material. Not suitable for blood or human fluids.

DESCRIPTION

Tube

TEFLON™ PTFE, co-extruded clear/white pigmented, smooth, phthalates free, tested in compliance with 1907/2006/CE (REACH). TEFLON™ PTFE is a polymer with excellent resistance to high temperature, mechanical stress and to oxidation. It complies with FDA 21 CFR 177.1550 standards, USP XXXVI class VI, ISO 10993 Sections 5,10,11:2009, EUROPEAN REGLEMENT 1935/2004/CE AND 10/2011/CE, 3A Sanitary Standard Class II

Reinforcement

synthetic plies, stainless steel wire helices, a/s wires to discharge static electricity

Cover

wide corrugated, EPDM, black, conductive, cloth finish. Abrasion, ageing and ozone resistant

Marking

red/white/blue tape

TUDERTECNICA TUFLUOR® PTFE CHEM

embossed according to norm EN 12115

TUDERTECNICA PTFE EN12115:2011 DN SD PN 10 BAR Ω Q/Y

TECHNICAL CHARACTERISTICS

Temperature range : -40°C / +150°C (-40°F / +302°F)

The operating temperature of the hose is directly dependent upon the specific fluid been conveyed and the length of time the fluid is in contact with the hose.

Electrical properties : type Ω according to norm EN 12115 (R<10⁶ Ω)

Norm : EN12115 - TRbF 131/2



Sterilization

refer to guidelines for cleaning and sanitizing on Tudertecnica website

Inside diameter		Outside diameter		Length		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[mt]	[ft]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
13	0,50	25	1,00	40	130	0,9	13	10	150	40	600	0,49	0,33	55	2,17
19	0,75	31	1,22	40	130	0,9	13	10	150	40	600	0,64	0,43	75	2,95
25	1,00	37	1,46	40	130	0,9	13	10	150	40	600	0,79	0,53	95	3,74
32	1,25	44	1,73	40	130	0,9	13	10	150	40	600	0,90	0,60	115	4,53
38	1,50	51	2,00	40	130	0,9	13	10	150	40	600	1,22	0,82	140	5,51
50	1,97	66	2,60	40	130	0,9	13	10	150	40	600	1,95	1,31	190	7,48
63,5	2,50	79,5	3,13	20	65	0,9	13	10	150	40	600	2,54	1,70	245	9,65
75	2,95	91	3,58	20	65	0,9	13	10	150	40	600	2,95	1,97	330	12,99
100	3,94	116	4,57	20	65	0,9	13	10	150	40	600	3,82	2,56	475	18,70

Data refer to ambient temperature (20°C).

We reserve the right to supply in random lengths shorter than 40mt or 20mt.